

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 December 2004 (09.12.2004)


PCT

(10) International Publication Number
WO 2004/106844 A2

- (51) International Patent Classification⁷: **G01B** (74) Agent: TRACY, Emery, L.; P.O. Box 1518, Boulder, CO 80306 (US).
- (21) International Application Number: PCT/US2004/015904 (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 20 May 2004 (20.05.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/472,347 21 May 2003 (21.05.2003) US
- (71) Applicant (for all designated States except US): UNIVERSITY OF WYOMING [US/US]; 16th and Gibbon, Laramie, WY 82071 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): ARMSTRONG, William, D. [US/US]; 1358 Indian Hills Drive, Laramie, WY 82072 (US). NAUGHTON, Jonathan [US/US]; 415 South 25th Street, Laramie, WY 82070 (US). LINDBERG, William, R. [US/US]; 619 South Eleventh, Laramie, WY 82070 (US).
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: OSCILLATORY MOTION BASED MEASUREMENT METHOD AND SENSOR FOR MEASURING WALL SHEAR STRESS DUE TO FLUID FLOW



Schematic of dynamic resonant shear stress sensor with the governing equation and a time history of the fluctuating shear force on the sensor (from a simulation). A cutaway view of the sensor is shown to display components below the surface.

(57) Abstract: A shear stress sensor for measuring fluid wall shear stress on a test surface is provided. The wall shear stress sensor is comprised of an active sensing surface and a sensor body. An elastic mechanism mounted between the active sensing surface and the sensor body allows movement between the active sensing surface and the sensor body. A driving mechanism forces the shear stress sensor to oscillate. A measuring mechanism measures displacement of the active sensing surface relative to the sensor body. The sensor may be operated under periodic excitation where changes in the nature of the fluid properties or the fluid flow over the sensor measurably changes the amplitude or phase of the motion of the active sensing surface, or changes the force and power required from a control system in order to maintain constant motion. The device may be operated under non-periodic excitation where changes in the nature of the fluid properties or the fluid flow over the sensor change the transient motion of the active sensor surface or change the force and power required from a control system

to maintain a specified transient motion of the active sensor surface.



Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.